



DGC3602



Retrocamera universale a foro. Angolazione retrocamera regolabile. Foro da 21,5mm tramite fresa in dotazione.
Dotata di 2 fili per: attivazione/disattivazione linee guida colorate (Bianco), inversione dell'immagine destra/sinistra (Blu).
Sistema NTSC. Si alimenta tramite il segnale che va alla lampadina di retromarcia (12V). **Nuovo sistema SLIM CABLE 5 metri.**
Permette l'accesso dei cavi anche in passaggi particolarmente angusti. Prolunga 5 metri disponibile DGPR5NEW.



25mm eyeball Class A car camera, Dual control
Image sensor: 1/3.7 PC6070 Chips
TV system: NTSC
Effective pixels: 720*488
Horizontal resolutions: 500 TV lines
Wide-angle: 170 Degree ,horizontal angle:125~135 Degree
Sensing area: 3.8 mm *2.9 mm
Shutter speed: 1-1/12000
Gamma no.:0.45
Minimum illumination:0.01 Lux/F=1.2(0 Lux with IR on)
Video output: RCA connector ,Other connector optional, 1.0 VP-P,75 OHM
Power consumption: 50mA
Power supply: DC12V
Operating temperature: -20°C - 75°C, RH 95% MAX
Storage temperature: -40°C- 80°C
Night vision Color camera
Waterproof rate:IP68