




# DGC770VN

## RETROCAMERA UNIVERSALE A FORO

RETROCAMERA A FORO UNIVERSALE. IL FILO PER SELEZIONARE IL MIRROR, PER QUESTA RETROCAMERA, **INVERTE LE IMMAGINI SOTTO/SOPRA** (E NON DESTRA/SINISTRA COME LE CLASSICHE CON MIRROR ON/OFF). FRESA IN DOTAZIONE E SI FISSA SOLITAMENTE IN ALTO NEI MEZZI COMMERCIALI IN MODO CHE L'OCCHIO GUARDI VERSO IL BASSO. SI ALIMENTA TRAMITE IL SEGNALE CHE VA ALLA LAMPADINA DI RETROMARCA. POSSIBILITA' DI ABILITARE O DISABILITARE LE LINEE GUIDA COLORATE. 12V. **DGC770VN SISTEMA NTSC**

RETROCAMERA DGC770V	CARATTERISTICHE
<p data-bbox="573 564 1162 592"><b>NON PUO' ESSERE INSTALLATA FRONTALMENTE</b></p>  <p data-bbox="1305 762 1514 863"><b>Selettore mirror verticale o orizzontale</b></p>  <p data-bbox="1279 979 1518 1007"><b>Linee guida on/off</b></p>  <p data-bbox="192 1075 707 1102"><b>INSTALLAZIONE IN MODALITA' VERTICALE</b></p>  <p data-bbox="271 1347 633 1374"><b>CAVO RCA 5m IN DOTAZIONE</b></p>  <p data-bbox="1182 1305 1536 1374"><b>INSTALLAZIONE IN MODALITA' ORIZZONTALE</b></p>	<p data-bbox="1570 564 2094 671">20mm con <b>mirror verticale on/off</b> camera, Night vision Color camera RH95%MAX</p> <p data-bbox="1570 683 1883 710">Image sensor: 1/4 PC7070</p> <p data-bbox="1570 721 1771 748">TV system: NTSC</p> <p data-bbox="1570 759 1872 786">Effective pixels: 640*480</p> <p data-bbox="1570 798 1995 825">Horizontal resolutions: 480 TV lines</p> <p data-bbox="1570 836 1995 863">Wide-angle: 170 Degree ,horizontal angle:85 Degree</p> <p data-bbox="1570 874 1939 901">Sensing area: 3.8 mm *2.9 mm</p> <p data-bbox="1570 912 2033 940">Shutter speed: 1-1/12000,Gamma no.:0.45</p> <p data-bbox="1570 951 1827 978">Waterproof rate:IP67</p> <p data-bbox="1570 989 2047 1016">Minimum illumination:0.01 Lux/F=1.2(0 Lux with IR on)</p> <p data-bbox="1570 1027 1921 1054">Video output: RCA connector</p> <p data-bbox="1570 1066 1957 1093">5m RCA cable, 1.0 VP-P,75 OHM</p> <p data-bbox="1570 1104 1912 1131">Power consumption: 130mA</p> <p data-bbox="1570 1142 1827 1169">Power supply: DC12V</p> <p data-bbox="1570 1181 1944 1208">Operating temperature: -20°C - 75°C, RH 95% MAX</p> <p data-bbox="1570 1219 1973 1246">Storage temperature: -40°C- 80°C</p>