



DGC772



Retrocamera universale a foro. Dotata di 3 fili per: attivazione/disattivazione linee guida colorate (Verde), inversione dell'immagine sotto/sopra (Arancio), inversione dell'immagine destra/sinistra (Bianco). Fresa in dotazione.

Sistema NTSC. Si alimenta tramite il segnale che va alla lampadina di retromarcia (12V). Nuovo sistema SLIM CABLE 5 metri.

Permette l'accesso dei cavi anche in passaggi particolarmente angusti. Prolunga 5 metri disponibile DGPR5NEW2.



TAGLIA IL FILO ARANCIO PER INVERSIONE
IMMAGINE SOTTO SOPRA



TAGLIA IL FILO BIANCO PER VISTA FRONTALE



TAGLIA IL FILO VERDE PER LINEE GUIDA



Fresa da 20mm in dotazione

Night vision Color camera

RH95%MAX

Image sensor: 1/4 PC7070

TV system: NTSC

Effective pixels: 640*480

Horizontal resolutions: 480 TV lines

Wide-angle: 170 Degree

Horizontal angle: 85 Degree

Sensing area: 3.8 mm * 2.9 mm

Shutter speed: 1-1/12000, Gamma no.: 0.45

Waterproof rate: IP67

Minimum illumination: 0.01 Lux/F=1.2

Video output: RCA connector

5m RCA cable, 1.0 VP-P, 75 OHM

Power consumption: 130mA

Power supply: DC12V

Operating temperature:

-20°C / 75°C, RH 95% MAX

Storage temperature: -40°C - 80°C