



DGCSIDE2



Retrocamera universale. Applicabilità tramite 2 viti o tramite bi-adesivo 3M in dotazione. Angolazione retrocamera regolabile.
Dotata di 2 fili per: attivazione/disattivazione linee guida colorate (Bianco), inversione dell'immagine destra/sinistra (Blu).
Applicabilità anche come camera laterale.

Sistema NTSC. Si alimenta tramite il segnale che va alla lampadina di retromarcia (12V). Nuovo sistema SLIM CABLE 5 metri.
Permette l'accesso dei cavi anche in passaggi particolarmente angusti. Prolunga 5 metri disponibile DGPR5NEW.



3M sticker mount camera with 7070 chips/dual switch
Special for rear windows mount
Image sensor: 1/4 PC7070
TV system: NTSC
Effective pixels: 640*480
Horizontal resolutions: 480 TV lines
Wide-angle: 170 Degree ,horizontal angle:85 Degree
Sensing area: 3.8 mm *2.9 mm
Shutter speed: 1-1/12000
Gamma no.:0.45
Minimum illumination:0.01 Lux/F=1.2(0 Lux with IR on)
Video output: RCA connector ,Other connector optional,
1.0 VP-P,75 OHM
Power consumption: 130mA
Power supply: DC12V
Operating temperature: -20°C - 75°C, RH 95% MAX
Storage temperature: -40°C- 80°C RH95%MAX
Waterproof rate:IP67
Night vision Color camera